

TSZJ66H 6*6 Shape Bracket Shape Type Tact Switch



Introduction

6×6 Light touch switch, light touch buttons, patch type light touch switch, pin type light touch switch, miniature light touch switch

Features

- Snap-in type, which can be directly mounted on PC board.
- Some of outout terminals can be also used as jumper leads, thus making circuit design easy.
- Available with anti-ESD ground terminal.
- Standard knobs are available.

Applications

- Operating switches in all types of electronic equipment such as audio devices, office devices, communication devices, measuring instruments, TVs, video recorders, automotive sets, etc.

Specification

Items		Standard
Operating temperature range		-30℃ to +85℃
Electrical performance	Rating	50mA. 12V DC
	Insulation resistance	100MW min. 100V DC
	Dielectric strength	250V AC for 1 min.
	Contact resistance	100mW max.
Durability	Lifetime	A:300,000 Cycles B: C:100,000 Cycles
Mechanical performance	Operating force	A:90gf B:180gf C:250gf
	Travel	0.25 ± 0.1mm

Diagram

No.	Dimensions					
1		<table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>L</th> <th>A</th> </tr> </thead> <tbody> <tr> <td>3.15</td> <td>3.5</td> </tr> </tbody> </table>	L	A	3.15	3.5
L	A					
3.15	3.5					

