

## Батареи CR литиевые



**CR-P2**



**2CR5**



**CR-V3**

Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Standard Discharge current(mA)	End Voltage (V)	Max. Diameter (mm)	Max. Height (mm)	Reference Weight (g)	Test Temperature (°C)
CR14250	3	650	10	2	14.5	25.0	10	23±3
CR14505	3	1500	10	2	14.5	50.5	17	23±3
CR17335	3	1500	10	2	17.0	33.5	16	23±3
CR17450	3	2000	10	2	17.0	45.0	25	23±3
CR17505	3	2300	10	2	17.0	50.5	28	23±3
CR17345(CR123A)	3	1500	10	2	17.0	34.5	16	23±3
CR11108(CR1/3N)	3	160	1	2	11.6	10.8	3.3	23±3
CR15H270(CR2)	3	850	10	2	15.6	27.0	11	23±3
CR-P2	6	1400	10	4	34.8X35.8X19.5		34	23±3
2CR5	6	1400	10	4	34X45X17		34	23±3
CR-V3	3	3000	20	2	29X14.5X52		34	23±3

### Таблица соответствия типоразмеров

1/2 AA	CR14250	Ø14.5x25.0
2/3AA	CR14335	Ø14.5x33.5
AA	CR14505	Ø14.5x50.5
CR123A	CR17335	Ø17.0x34.5
bir	CR18505	Ø18.8x50.5
C	CR26500	Ø26.2x50.0
D	CR34615	Ø34.0x61.5