

# Shoulder 好达

SHOULDER ELECTRONICS CO., LTD.

## CERAMIC RESONATOR Data Sheet

PRODUCT 产品: CERAMIC RESONATOR

MODEL NO 型号: ZTACC....MG

PREPARED 编制: Fengyu

CHECKED 审核: York

APPROVED 批准:

DATE 日期: 2007-01-25

---

## 1. Scope


The specification is fit for ceramic resonator 1.84-8.00MHz.

## 2. Part Number: ZTACC ..MG


## 3. Electrical Characteristics

| No.  | Item  | Characteristics |
|------|---|-----------------|
| 3-1  | Oscillate Frequency (MHz)                                       | 1.84-8.00       |
| 3.2  | Frequency Tolerance max   | ±0.5%           |
| 3.3  | Resonant Impedance max ( $\Omega$ )                             | 100             |
| 3.4  | Built – in Capacitance (PF)                                     | --              |
| 3.5  | Insulate Resistance min (M $\Omega$ )                           | 100             |
| 3.6  | Withstanding Voltage D.C (V)                                    | 100 (max 5 sec) |
| 3.7  | Voltage<br>(1) D.C Voltage max (V)<br>(2) Input Voltage max (V) | 6<br>15Vp-p     |
| 3.8  | Temp characteristics of Oscillate frequency max                 | ±0.3%           |
| 3.9  | Operating Temp Range ( $^{\circ}\text{C}$ )                     | -20 ~ +80       |
| 3.10 | Storage Temp ( $^{\circ}\text{C}$ )                             | -55 ~ +85       |

## 4. Test Circuit



## 5. Dimension



## 6. Physical and Environmental Characteristics

| No  | Item             | Condition of Test  | Performance Requirements                        |
|-----|------------------|--|---|
| 6.1 | Humidity         | Keep the resonator at $40 \pm 2^\circ\text{C}$ and 90-95% RH for $96 \pm 4$ hours. Then release the resonator into the room condition for 1 hour prior to the measurement. | It shall fulfill the specifications in Table 1. |
| 6.2 | Vibration        | Subject the resonator to vibration for 2 hours each in x,y and z axis with the amplitude of 1.5mm, the frequency shall be varied uniformly between the limits of 10-55Hz   | It shall fulfill the specifications in Table 1. |
| 6.3 | Mechanical Shock | Drop the resonator randomly onto a concrete floor from the height of 100 cm 3 times.   | It shall fulfill the specifications in Table 1. |
| 6.4 | Soldering Test   | Passed through the re-flow oven under the following condition and left at room temperature for 1 hour before measurement.  | It shall fulfill the specifications in Table 1. |


|     |                           |   |                 |   |
|-----|---------------------------|---|-----------------|---|
|     |                           | Temperature at surface of the substrate   | Time            |   |
|     |                           | Preheat $150\pm 5^{\circ}\text{C}$  | $60\pm 10$ sec. |   |
|     |                           | Peak $240\pm 5^{\circ}\text{C}$   | $10\pm 3$ sec.  |   |
| 6.5 | Solder Ability            | Dip the resonator terminals into the solder bath at $230\pm 5^{\circ}\text{C}$ for $3\pm 0.5$ sec.  |                 | More than 95% of the terminal surface shall be covered. |
| 6.6 | High Temperature Exposure | Subject the resonator to $80\pm 5^{\circ}\text{C}$ for $96\pm 4$ hours. Then release the resonator into the room conditions for 1 hour prior to the measurement.  |                 | It shall fulfill the specifications in Table 1.         |
| 6.7 | Low Temperature           | Subject the resonator to $-20\pm 5^{\circ}\text{C}$ for $96\pm 4$ hours. Then release the resonator into the room conditions for 1 hour prior to the measurement.   |                 | It shall fulfill the specifications in Table 1.         |
| 6.8 | Temperature Cycling       | Subject the resonator to $-20^{\circ}\text{C}$ for 30 minutes followed by a high temperature of $85^{\circ}\text{C}$ for 30 min. Cycling shall be repeated 5 times with a transfer time of 15 second at the room condition for 1 hour prior to the measurement. |                 | It shall fulfill the specifications in Table 1.         |

TABLE1


| Item                         | Specification                 |
|------------------------------|-------------------------------|
| Oscillation Frequency Change | $\Delta F/F_0 \leq 0.3\%$ max |
| Resonant Impedance           | $\Delta R_0 \leq \pm 10$ Ohm  |

7.

RECOMMENDED REFLOW SOLDERING STANDARD CONDITIONS



## 8. Packing



Tape Dimension (mm)

|    | A<br>±0.2 | B<br>±0.2 | C<br>±0.3 | D<br>±0.1 | E<br>±0.1 | F<br>±0.1 | G<br>±0.1 | H<br>±0.1 | ØJ<br>±0.1 | ØN<br>±0.1 | M<br>max        | R<br>max | K<br>±0.2 | T<br>±0.1 |
|----|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|------------|------------|-----------------|----------|-----------|-----------|
| MG | 3.8       | 7.8       | 16.0      | 7.5       | 1.75      | 8.0       | 4.0       | 2.0       | 1.5        | 1.6        | 10 <sup>µ</sup> | 0.3      | 2.1       | 0.3       |
| MT | 5.0       | 4.4       | 12.0      | 5.5       |           |           |           |           |            |            |                 |          | 1.8       |           |
| MX | 3.4       | 4.0       | 12.0      | 5.5       |           |           |           |           |            |            |                 |          | 1.3       |           |

Standard Package: 4Kpcs / reel