

# LARGE CAN TYPE

# HS

Series

Wide Temperature Range, Miniature Sized

JAMICON®

- Smaller case sized than HP series.
- Withstanding 2000 hours application of high ripple current at 105°C.




## ● SPECIFICATION


Item	Characteristic															
Operation Temperature Range	-40 ~ +105°C															
Rated Working Voltage	16 ~ 500VDC															
Capacitance Tolerance (120Hz 20°C)	±20%(M)															
Leakage Current (20°C)	$I \leq 0.02CV$ or 3 (mA) *Whichever is smaller after 5 minutes I : Leakage Current(μA) C : Rated Capacitance(μF) V : Working Voltage(V)															
Surge Voltage (20°C)	W.V.	16	25	35	50	63	80	100	160	180	200	250	350	400	450	500
	S.V.	20	32	44	63	79	100	125	200	225	250	300	400	450	500	550
Dissipation Factor (tan δ) (120Hz 20°C)	Rated Voltage (V)	16		25		35		50		63		80		100		≥160
	Capacitance	≤33,000	≥47,000	≤33,000	≥47,000	≤22,000	≥27,000	≤6,800	≥10,000	≤6,800	≥10,000	≤3,300	≥4,700	≤3,300	≥4,700	—
	tan δ	0.50	0.60	0.40	0.50	0.35	0.40	0.30	0.35	0.25	0.35	0.20	0.25	0.20	0.25	0.15
Low Temperature Stability	Impedance ratio at 120Hz															
	Rated Voltage (V)	16		25		35		50		63~100		160~250		350~500		
	-25°C / +20°C	6		6		6		4		3		4		6		
	-40°C / +20°C	15		15		10		8		6		—		—		
Load Life	After 2000 hours application of W.V. at +105°C the capacitor shall meet the following limits.															
	Capacitance Change	≤ ±20% of initial value														
	Dissipation Factor	≤ 175% of initial specified value														
	Leakage current	≤ initial specified value														
Shelf Life	At +105°C, no voltage application after 1000 hours, the capacitor shall meet the limits for load life characteristics. (With voltage treatment)															

## ● TERMINAL TYPE



### ▲ P.C.B. TERMINAL (SNAP IN) SYMBOL:W(φ22~35)





### ▲ LUG TERMINAL SYMBOL:G(φ22~35)



### ▲ P.C.B. TERMINAL SYMBOL:V(φ25~35)



### (φ35) A.B. blank terminals



## ● RIPPLE CURRENT COEFFICIENTS

Temperature(°C)	40	60	70	85	105
Multiplier	2.50	2.20	2.00	1.80	1.00

Frequency(Hz)	60	120	400	1k	10k
W.V.	Multiplier				
≤100V	0.80	1.00	1.10	1.20	1.20
≥160V	0.80	1.00	1.10	1.30	1.40

※ For φ45 dimension, refer to page 14.

## ● CASE SIZE & MAX RIPPLE CURRENT

Case size : D x L (mm)  
 Max ripple current : A (rms)  
 (R.C.) : 105°C 120Hz

μF	V(Code) Code φD	16 (1C)					25 (1E)					35 (1V)					50 (1H)				
		22	25	30	35	45	22	25	30	35	45	22	25	30	35	45	22	25	30	35	45
1500	152																25				
																	1.05				
2200	222														25						
															1.17						
3300	332														30	25					
															1.43	1.36					
4700	472														35	30	25				
															1.36	1.58	1.56				
6800	682														50	40	30	25			
															2.09	1.94	1.82	1.96			
10000	103														50	35	30				
															2.24	2.03	2.20				
15000	153																				
22000	223																				
27000	273																				
33000	333																				
47000	473																				
56000	563																				

μF	V(Code) Code φD	63 (1J)					80 (1K)					100 (2A)					160 (2C)				
		22	25	30	35	45	22	25	30	35	45	22	25	30	35	45	22	25	30	35	45
330	331																				
390	391																				
470	471																				
560	561																				
680	681																				
820	821																				
1000	102																				
1200	122																				
1500	152																				
1800	182																				
2200	222																				
3300	332																				
3900	392																				
4700	472																				
6800	682																				
8200	822																				
10000	103																				
12000	123																				
15000	153																				
18000	183																				

L(mm)  
R.C.



## ● CASE SIZE & MAX RIPPLE CURRENT

Case size : D x L (mm)  
 Max ripple current : A (rms)  
 (R.C.) : 105°C 120Hz

μF	V(Code) Code φD	350 (2V)					400 (2G)					450 (2W)					500 (2H)								
		22	25	30	35	45	22	25	30	35	45	22	25	30	35	45	22	25	30	35	45				
47	470											25					25								
												0.39					0.27								
68	680						25					30	25				30	25							
							0.47					0.50	0.50				0.35	0.35							
82	820	25					30	25				35	30				35	30							
		0.43					0.56	0.56				0.59	0.60				0.41	0.41							
100	101	30	25				30	25				40	35	25			40	35	30						
		0.51	0.51				0.61	0.61				0.69	0.70	0.68			0.47	0.48	0.50						
120	121	30	25				35	30	25			45	35	30	25		50	40	35	25					
		0.55	0.55				0.72	0.73	0.75			0.80	0.77	0.80	0.82		0.57	0.56	0.59	0.56					
150	151	35	30	25			40	35	30			45	35	30			45	40	30						
		0.66	0.67	0.69			0.85	0.86	0.90			0.96	0.96	0.99			0.66	0.69	0.68						
180	181	40	35	30			45	40	30	25		50	35	30			50	40	35						
		0.77	0.78	0.82			0.98	1.00	0.99	1.01		1.10	1.05	1.08			0.75	0.76	0.79						
220	221	50	40	30	25		45	35	30			40	35				45	40							
		0.94	0.91	0.90	0.92		1.17	1.16	1.20			1.22	1.27				0.88	0.92							
270	271		45	35	30		50	40	30			50	40				50	45							
			1.07	1.06	1.10		1.35	1.36	1.33			1.49	1.48				1.02	1.07							
330	331		50	40	30			45	35				45					50							
			1.23	1.24	1.21			1.58	1.56				1.72					1.23							
390	391			45	35				40				50												
				1.42	1.40				1.79				1.96												
470	471				40				45																
					1.62				2.07																
560	561				45				50																
					1.86				2.36																
680	681																55								
																	2.49								
820	821									50							65								
										2.72							2.93								
1000	102					55				60															
						2.59				3.24															
2200	222					65																			L(mm)
						4.12																			R.C.