



Features

- ▶ Miniature ceramic package
- ▶ High shock & vibration resistance
- ▶ Military temperature range -55+125°C option
- ▶ Low power consumption

Specifications

Parameters	Product	Option Code
	CC7A	
Terminations: Gold plated pads Sn/Ag/Cu plated pads	<input checked="" type="checkbox"/> <input type="checkbox"/>	T1A T3A
Frequency range: 24.0 ~ 50.0MHz	<input checked="" type="checkbox"/>	
Calibration tolerance: ±50ppm Other	<input checked="" type="checkbox"/> <input type="checkbox"/>	specify
Temperature stability / range: ±50ppm over -40 to +85°C ±100ppm over -55 to +125°C Other	<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	M specify
Storage temperature range: -55 to +125°C	<input checked="" type="checkbox"/>	
Circuit condition: 3pF 9pF 16pF	<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>	specify specify specify
Static capacitance (C₀): 0.7pF typ	<input checked="" type="checkbox"/>	
Motional capacitance (C₁): 1.0fF typ, 3.0fF max	<input checked="" type="checkbox"/>	
Equivalent series resistance: 60Ω typ, 100Ω max	<input checked="" type="checkbox"/>	
Ageing: ±3ppm max first year	<input checked="" type="checkbox"/>	
Drive level: 100μW typ, 250μW max	<input checked="" type="checkbox"/>	
Shock resistance: 5,000g, 0.3ms, ½ sine	<input checked="" type="checkbox"/>	
Vibration resistance: 20g, 10.0 ~ 2,000Hz	<input checked="" type="checkbox"/>	
Soldering condition: Reflow, 260°C, 20 sec max	<input checked="" type="checkbox"/>	

■ Standard. □ Optional - Please specify required code(s) when ordering

Ordering Information

Product name + termination + option codes (if any) + frequency + circuit condition

eg: **CC7A-T1A 24.0MHz 9pF** ±50ppm -40+85°C

CC7A-T1A/M 26.0MHz 16pF ±100ppm -55+125°C

Option code X (eg CC7A-T1A/X) denotes a custom spec.

- ◆ Available on T&R 1k, 3k or 14k pcs/reel.
- ◆ Refer to our website for T&R and soldering details.
- ◆ Ask about higher shock & vibration specifications.