


受 控

## SPECIFICATION

- 1. Rated Voltage ..... 6VDC
- 2. Operating Voltage ..... 4~8VDC
- 3. Max. Rated Current ..... 40mA/6VDC
- 4. Min. Sound Pressure Level ..... 85dB/10cm
- 5. Resonant Frequency ..... 2300±300Hz
- 6. Response Time ..... 50ms
- 6. Case Material ..... PBT
- 7. Operating Temperature ..... -25~+70°C
- 8. Store Temperature ..... -30~+80°C
- 9. Weight ..... 2g



				<b>KEPO</b> NINGBO KEPO ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
				<b>Magnetic Buzzer QUARTZ-1</b>	
				<b>DAP1206X</b>	
No.	DESCRIPTION	APPROVED	DATE		
TOLERANCES UNLESS NOTED OTHERWISE X * XX * XXX * °° FORMED °° ANGLES °°		APPROVALS		DATE	
		DRAWN	胡治健		
		CHECKED			UNIT
		APPROVED			DWG NO.
				mm	OEM2690
				SCALE	SHEET
				18.04.17	VER 1.1
				NOT TO SCALE	