

Specification for Speaker	Page	2/9
	Revision No.	1.0
Model No. : KPB3525-EM810-5905	Drawing No.	KFC5905

## CONTENTS

1. Scope
2. General
3. Electrical and Acoustic Characteristics.
4. Reliability Test
5. Measurement Block Diagram & Response curve
6. Structure
7. Dimensions
8. Packing
9. Revision

# Specification for Speaker

Page

3/9

Model No. : KPB3525-EM810-5905

Revision No.

1.0

Drawing No.

KFC5905

## 1. Scope

This specification is applied to the dynamic speaker which is used all of the electrical acoustic product.

-- compact, rich sound

-- applications: mobile phone, PDA, notebook computer, etc. ..

## 2. General

2.1 Out-Diameter : 35x25 mm

2.2 Height : 6.6 mm

2.3 Weight : 15 g

2.4 Operating Temperature range:

-20~+50℃ without loss of function

2.5 Store Temperature range:

-40~+60℃ without loss of function

## 3. Electrical and Acoustic Characteristics.

Test condition : 15 ~ 35 ℃, 25% ~ 85% RH, 860~1060 mbar

No	Items	Specification
1	Impedance	8 Ω ± 15% (1Vrms at 1KHz)
2	Sound Pressure Level	91 dB ± 3dB (0.1w/0.1m average at 1.0,1.2,1.5,2kHz)
3	Resonance Frequency	900 Hz ± 20%
4	Frequency Range	Fo ~20KHz
5	Input Power	Rated 1.5 W / Max. 2 W
6	Distortion	<10% Max. at 2kHz/1Vrms
7	Buzz and Rattle	Should not be audible buzzes,rattles when the 3.46V sine wave signal swept at frequency range.
8	Polarity	When supplied plus D.C. voltage to (+) terminal, the cone diaphragm must move to forward.

# Specification for Speaker

Page

4/9

Revision No.

1.0


Model No. : KPB3525-EM810-5905

Drawing No.


KFC5905

## 4. Reliability Test

After test(1~7item), the speaker S.P.L . difference shall be within  $\pm 3\text{dB}$ , and the appearance not exist any change to be harmful to normal operation (e.g. cracks,rusts,damages and especially distortion).

No	Items	Specification
1	High Temperature Test	After being placed in a chamber with $+60\pm 3\text{ }^\circ\text{C}$ for 96 hours and then being placed in natural condition for 1 hour, speaker shall be measured.
2	Low Temperature Test	After being placed in a chamber with $-40\pm 3\text{ }^\circ\text{C}$ for 96 hours and then being placed in natural condition for 1 hour, speaker shall be measured.
3	Humidity Test	After being placed in a chamber with 85 to 90%R.H. at $+40\pm 2\text{ }^\circ\text{C}$ for 96 hours and then being placed in natural condition for 1 hour, speaker shall be measured.
4	Thermal Shock Test	<p>After being placed in a chamber at <math>+50\text{ }^\circ\text{C}</math> for 1 hour, then speaker shall be placed in a chamber at <math>-20\text{ }^\circ\text{C}</math> for 1 hour(1 cycle is the below diagram).</p> <p>After 6 above cycles, speaker shall be measured after being placed in natural condition for 1 hour.</p> 
5	Vibration Test	After being applied vibration of amplitude of 1.5mm with 10 to 55Hz band of vibration frequency to each of 3 perpendicular directions for 1 hour, then placed in natural condition for 1 hour, speaker shall be measured.
6	Drop Test	The speaker when mounted in the jig which weight 85g~100g, shall with stand 15 times random drops from a height of 1.5 meter to a concrete floor faced with 5mm thick hard wood board.and be nothing mechanical damage.
7	Load test	After being applied loading white noise with input power 1.5W(3.46Vrms.) for 96 hours, then placed in natural condition for 1 hour, speaker shall be measured.
8	Insulation test	When they are measured with DC 100V the insulation resistance between v.c. terminal and frame must be more than $1\text{ M}\Omega$


### 5. Measurement Block Diagram & Response curve



[dB/20.0u Pa]

Output Response (Signal) - Input (Magnitude)

Working : Input : Input : SSR Analyzer



# Specification for Speaker

Page

6/9

Revision No.


1.0

Model No. : KPB3525-EM810-5905

Drawing No.

KFC5905

## 6. Structure



No.	Part Name	Q'ty	Material	Remarks
8	Terminal	1	FR-4	
7	YOKE	1	SPCC	
6	Magnet	1	Nd-Fe-B	
5	Plate	1	SPCC	
4	V-coil	1	Lock bobbin	
3	Diaphragm	1	Pu+paper	
2	Frame	1	PET	
1	BOX	1	ABS	

# Specification for Speaker

Page

7/9

Revision No.






1.0

Model No. : KPB3525-EM810-5905

Drawing No.

KFC5905

## 7. Dimensions



FIRST ANGLE PROJECTION



UNIT : mm

Tolerance : ±0.3

# Specification for Speaker

Page

8/9

Revision No.

1.0

Model No. : KPB3525-EM810-5905

Drawing No.

KFC5905

## 8. Packing

Each minimum package unit of products shall be in a carton box and it shall be clearly marked with Part Number, quantity and outgoing inspection number.

There shall be no mechanical damage on products during transportation and/or in storage.

Specification for Speaker		Page	9/9
Model No. : KPB3525-EM810-5905		Revision No.	1.0
		Drawing No.	KFC5905

### 9. Revision

Rev. No.	DATE	PAGE	DESCRIPTION	BOM
1.0	2010-9-6		Primary	