



SPECIFICATION

- 1. Rated Voltage 3 V
- 2. Operating Voltage 2~5 V
- 3. Max. Rated Current 60 mA
- 4. Coil Resistance 25±4 Ω
- 5. Coil Impedance 45 Ω
- 6. Min. Sound Pressure Level 85dB/10cm
- 7. Resonant Frequency 2731Hz
- 8. Shell Material/Color..... PBT/Black
- 9. Operating Temperature -20~+70°C
- 10. Store Temperature -30~+80°C
- 11. Weight 1g

Compliance with ROHS

KEPO NINGBO KEPO ELECTRONIC CO.,LTD
<http://www.chinaacoustic.com>

Magnetic Transducer
 KPMG09C1-K4032

TOLERANCES UNLESS NOTED OTHERWISE X = ±0.1 XX = ±0.05 XXX = ±0.02 90° FINISHED ±0.1° ANGLES ±0.1°	APPROVALS	DATE	DATE	DATE
FIRST ANGLE PROJECTION	DRAWN	CHECKED	APPROVED	DATE
	楼海江	09.04.13		

UNIT	mm	DWG NO.	OEM4032R	SCALE	NOT TO SCALE	SHEET	VER	1.0
------	----	---------	----------	-------	--------------	-------	-----	-----