



是否丝印及内容根据生产任务单要求

SPECIFICATION

1. Rated Voltage.....12VDC
2. Operating Voltage.....9~16VDC
3. Rated Current.....600mA at 12VDC
4. Flash Mode Rated Current.....130mA at 12VDC
5. Waiting Rated Current.....80mA at 12VDC
6. Max.Sound Pressure Level.....108dB at 12VDC/100cm
7. Tone Nature.....Siren
8. Flash Frequency.....2Hz
- 9.LED Frequency.....0.6Hz
10. Sound Frequency Range.....2.0KHz~3.5KHz
11. Case Material.....ABS
12. Operating Temperature.....-20℃~+60℃
13. Store Temperature.....-40℃~+80℃
14. Humidity95%R.H. at +40℃
15. Weight.....1.0Kg

No.		DESCRIPTION		APPROVED	DATE	KEPO NINGBO KEPO ELECTRONIC CO.,LTD http://www.chinakepo.com
TOLERANCES: UNLESS NOTED OTHERWISE: mm ± °XX ± °XXX ±		DRAWN		APPROVALS	DATE	
FIRST ANGLE PROJECTION		CHECKED		陈龙		UNIT: mm DWG NO: KT3.007.004.01
		APPROVED			09.4.20	SCALE: NOT TO SCALE SHEET: VER: 1.0