

CERAMIC SMD TYPE STG



- Temperature Compensated Crystal Oscillator
- Clipped Sinewave Output
- 3.0 supply voltage
- Surface mount package

ELECTRICAL SPECIFICATIONS

	CLIPPED SINEWAVE
Frequency Range	12.000 to 26.000MHz
Operating Temperature Range	0°C ~ + 50°C to -40°C ~ 85°C
Storage Temperature Range	-55°C ~ 125°C
Frequency / Stability Vs. Operating Temperature Range Vs. Input Voltage (±5%) Vs. Load(±10%) Vs. Aging	See Table 2 ±0.3ppm max. ±0.3ppm max. ±1.0ppm max.
Supply Voltage(V _{DD})	3.3V to 5.0V
Input Current	2mA to 5mA
Output Level	0.8Vp-p(V _{DD} 3.3V), 1.0Vp-p(V _{DD} :5.0V)
Load Drive Capability	10kΩ // 10pF
Frequency Deviation	±5ppm or ±10ppm minimum Over Control Voltage


Part Numbering Guide

MODEL (PKG TYPE)	SUPPLY VOLTAGE	FREQUENCY STABILITY	OPER-TEMP RANGE	OUTPUT	DEVITON	PACKING	FREQUENCY (MHZ)
STG	3 : 3.3V(3.0V)	TABLE2 REFERENCE	TABLE2 REFERENCE	S : ONLY	5 : ONLY	BLANK : BULK R : TAPE & REEL	xx.xxx(STD) xx.xxxxxx

Table2.

		FREQUENCY STABILITY vs. TEMPERATURE RANGE								
Temp	Stability	±1.0ppm	±1.5ppm	±2.0ppm	±2.5ppm	±3.0ppm	±3.5ppm	±4.0ppm	±4.5ppm	±5.0ppm
		10	15	20	25	30	35	40	45	50
0 ~ 50°C	A	*	*	*	*	*	*	*	*	*
-10 ~ 60°C	B		*	*	*	*	*	*	*	*
-10 ~ 70°C	C		*	*	*	*	*	*	*	*
-20 ~ 70°C	D			*	*	*	*	*	*	*
-30 ~ 60°C	E				*	*	*	*	*	*
-30 ~ 70°C	F				*	*	*	*	*	*
-30 ~ 75°C	G				*	*	*	*	*	*
-40 ~ 80°C	H				*	*	*	*	*	*
-40 ~ 85°C	I				*	*	*	*	*	*

MECHANICAL DIMENSIONS (mm)



LAND PATTERN (mm)

